

Omnisports TRAINING



KEY POINTS

Description :

Vinyl sports floor covering over fibreglass with PVC foam backing. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance)

Type of installation :

- Glued Installation

Surface Texture :

Sorrent

Compatible Installation :

Association possible with a sub construction (Lumaflex type)

Installation instructions and maintenance guide :

On request

Dimensions (EN 426/EN 427) :



2 m



20.5 lm or 23 lm

Total thickness (EN 428) :



5.0 mm (± 0,15mm)

Total weight (EN 430) :



4.23kg/m² (± 500g)

Technical data in force as from the date of publication (05/2013). The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.

For more detailed technical information, please contact Tarkett.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

Properties	Standard	Omnisports TRAINING
Vinyl Indoor sports flooring with elastic point area deformation		
Must be installed on a sub-construction to reach the requirements of the EN 14 904 standard		
Sports properties		
Friction	EN 13036-4	100
Shock Absorption %	EN 14 808	19
Vertical deformation	EN 14 809	1 mm
Vertical ball rebound	EN 12235	98.4%

Classification		
Reaction to fire	EN 13501-1	Cfl-S1 Glued installation
Hygiene	-	Does not contribute to infection spreading

Technical characteristics		
Wear Layer	EN 429	0.70 mm
Resistance to wear	EN ISO 5470-1	0.13 g
Resistance to indentation	EN 1516	0.16mm
Behaviour under a rolling load	EN 1569	0.22mm
Resistance to impacts	EN 1517	Some marks, No degradation

Specific characteristics		
Surface treatment	Topclean X-treme performance protection	
Maintenance		

COMPATIBLE SLABS: Concrete, asphalt screed, anhydrite screed. Any deviation of the slab must be corrected prior installation (6 mm under a 3 m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.

Omnisports Training



51%
Natural

100%
21%
Recyclable
Recycled content



*TVOC AT 28 DAYS



CE 2010	EN 14041:2004 	Manufactured by: Tarkett France 08200 Sedan FRANCE EN 14041 Omnisports Speed/Training
-------------------	-----------------------	---

Tarkett France – 2, rue de l'Égalité – 92748 Nanterre cedex – TÉL. +33(0)1 41 20 40 40 – FAX +33(0)1 41 20 47 05 – info@tarkett.com
S.A.S au capital de 30800000 euros – RCS Nanterre 410 081640
www.tarkett-sports.com